# Extender

Extender is an additive for Arboritec water borne lacquers. It improves the leveling and prolongs the working time for both primers and top coats.
Adding 2% Extender reduces the tendency for roller marks or discoloring, in bad indoor climate conditions (high temperatures, low humidity) or in large areas.

## INSTRUCTIONS

Add 2% Extender to the water borne primer or top coat and shake/stir well. If using with 2 component systems add the extender before adding the hardener.
Do not use below 14°C.
Please consult safety data sheet for further information.

**Package:** 16x100ml

**Storage:** Best before 2 years at +5°C to +25°C in unopened package. Keep out of the range of children.

## HEALTH AND ENVIRONMENT

Use the normal due care when handling chemical products. Use protective goggles and gloves if there is any risk of splashing. If the product comes into contact with your skin, wash it off with soap and water. If the product gets into your eyes, rinse with a generous amount of water. For further information see Safety Data Sheet.

**Extender** 100ml

Extender is an additive for Arboritec/Nanofloor water borne and prolongs the working time for both primers and top coats. Adding 2% Extender reduces the tendency for roller marks (high temperatures, low humidity or in large areas.

**INSTRUCTIONS:** Add 2% Extender to the water borne. If using with 2 component systems add the extender before. Do not use below 14°C. Please consult safety data sheet. **Storage:** Best before 2 years at +5°C to +25°C in unopened. Keep out of the range of children.

**Arboritec AB**, Olof Wijksväg 9, 444 65 Jörlanda, Sweden +46 303 56 330 www.arboritec.com / www.nanofloor.

This Arboritec Product Sheet is intended for advice only. The figures apply to normal conditions, which may vary due to means of application, temperature etc. We retain the right to make changes and amendments without prior notice.

A safety data sheet is available for professional users on request. Keep out of the reach of children.

For technical advice: Contact your distributor or Arboritec Technical Service at +46 303 56330